


Power System Restoration - The Graceful Degradation Phase

Mike Adibi, IRD Corporation
Bethesda, Maryland, USA
madibird@aol.com

(c) IRD 2004

1

Major Power System Disturbances



(c) IRD 2004

2

Major Power System Disturbances

Given: that blackouts are likely to occur,

What can be done to: reduce their impact (i.e., their extent, intensity and duration)?

Major Power System Disturbances Sequence of Events

System	====>	Northeast	PJM
Year	====>	1965	1967
Event	Initial	0	0
Islands	Numbers	5	3
Formed	Seconds	7	5
Blackout	Minutes	12	9
Restored	Hours	13	8


Federal Power Commission Reports

Major Power System Disturbances After the Initial Cause

They may result in islands with:

- Insufficient generation (**load-rich**) experiencing a decay in system frequency, or
- Insufficient load (**generation-rich**) experiencing a rise in system frequency

Turbine Blade Damage Bucket Limit Calculation



Immediately After the Initiating Cause

Frequency rise and decay are automatically arrested by:

- Load rejection,
- Load shedding,
- Low frequency isolation scheme, and
- Controlled islanding.

Immediately After the Initiating Cause

Success rate:

Over fifty percent !

Challenge:

Coordination of control and protective systems between power plants and electrical system.

Load Rejections

Generation Rich

To match generation with load, load rejections are used

Full-load Rejection:


- The main generator breaker trips
- Loss of synchronization and full-load
- Steam generators **runback** from full-load to no-load (7%).

Partial-load Rejection:

- The main generator breaker remains closed
- Loss of partial load (10 to 30%)
- Steam generator usually requires **no-runback**


Basic System for Load Rejection

(Boiler: 10^6 pph, $>3,000$ psi, $>10^3$ °F)



TCV: Turbine Control Valve,
 IV : Intercept Valve,
 CV : Check Valve

Intercept “Fast Valving”



(c) IRD 2004

11

Load Rejection Performance

Depends on % of PLR

- Germany: One in two (50%)
- France: One to four in five (20 to 80%)
- Ontario Power: Eight in twelve reactors (66%)¹
- Italy: Few thermal units successfully load-rejected²
- USA: Analysis of 50 BTG trips, 30% due to TG, 42% due to BT & 28% due to operators³

1. Blackout of August 14, 2003

2. Blackout of September 28, 2003

3. Very few operational, primarily due to conservative operating philosophy

(c) IRD 2004


12

Under-frequency Load Shedding

Load Rich

To match load with generation, under-frequency load shedding is used:

- Number of frequency step, 3
- Frequency set points, 59.3, 58.9 and 58.5Hz
- Load shed per step, 10%
- Fixed time delay per step, 5-8 cycles
- Correct operation of over 50%




Under-frequency Load Shedding

- Shed radial feeders, interrupting many small loads
- Restore the interrupted load manually at about 59.3 Hz
- Have experienced incorrect operation at high and low temperatures
- Have observed difference in frequency as much as 0.2 Hz
- Assume the change in load as 0.5% per 0.1 Hz

(c) IRD 2004


15

Low Frequency Isolation Scheme After the Initial Event



(c) IRD 2004

16



Low Frequency Isolation Schemes Performance

Over 50 US utilities have successfully used LFIS to isolate one or more generators with matching loads.

The majority:

- Use automatic under-frequency relay to initiate the action,
- Select generators for isolation,
- Set the under-frequency relay between 58 and 58.5 Hz., &
- Allow time delay of 6 to 8 cycles, and

(c) IRD 2004 18

Controlled Islanding

After the Initial Event


- Initial Events: Faults occur and are cleared
in milli-seconds
- Subsequent Effects: Systems separate into islands
in seconds
- Final Results: Load & gen. imbalance causes blackout
in minutes

Conjectures

(Not Fully Verified)

- Out-of-Step Location:
Depends on the prevailing system configuration and load level,
Is independent of initial fault location or fault intensity, and
Occurs one operation at a time (cascades) with adequate time interval.
- Transfer Tripping Locations:
Split the system into two parts (islands), and
Each part having minimal load and generation imbalance.


Figure 2 - Swing Curves Under Heavy-Load Condition



(c) IRD 2004

21


Figure 6 - Angle-Impedance relay (Buffer or Blinder)



(c) IRD 2004

22


Figure 4 - Apparent Impedance Path
Line 136-135



(c) IRD 2004

23


Figure 3 - Swing Curves Under Light-Load Condition



(c) IRD 2004

24

Figure 5 - Apparent Impedance Path
Line136 - 139



(c) IRD 2004

25

Real Time Controlled Separation

Out-of-step blocking relays:

- Prevent separation where there is heavy power flow (**unbalanced load and generation**).

Transfer tripping relays:

- Allow separation where there are light power flows (**balanced load and generation**).

(c) IRD 2004

26

The Graceful Degradation Phase

Past Experience:

The probability of success in retaining initial sources of power by:

- Full and Partial Load Rejections,
- Under-frequency Load Shedding
- Low Frequency Isolation Schemes,
- Controlled System Separation, and


has been greater than 50%.

Future Challenge:

Need better control & protection coordination between:

- Prime mover's (BTG), and
- Electrical systems.

Restoration Stages **After Subsequent Effect**



After the Subsequent Effect Partial or Complete Blackout

Load and generation are manually balanced by:

- Starting with the initial sources of power, and
- Supplying the critical loads in the priority order.

After the Subsequent Effect Partial or Complete Blackout

Success rate:

Complete blackouts need improvements.

Challenge:

Coordination of actions by power plants and electrical system operators.

Power System Restoration

After Subsequent Effect

The tasks are to:

- List and rank the critical loads by **priority**,
- List and rank the initial sources of power by **availability**, and
- Determine the most effective ways of bringing the two together.

Initial Critical Loads

After Subsequent Effect

- | | Priorities |
|-----------------------------------|-------------------|
| • Cranking Drum-Type Units | High |
| • Pipe-Type Cables Pumping System | High |
| • Transmission Stations | Medium |
| • Distribution Stations | Medium |
| • Industrial Loads | Low* |
- Is Used in the Initial Stage to An Advantage

Initial Sources of Power After Subsequent Effect

	Minutes	Success Probability
Run-of-the-River Hydro	5-10	High
Pump-Storage Hydro	5-10	High
Combustion Turbine	5-15	Medium (50%)
Tie-Line with Adjacent Systems	Short	Not Relied On *

* Policy: Provide Remote Cranking Power

Restoration After a Blackout

Preparation Stage (1 to 2 Hours)

- Evaluate Pre-Disturbance Condition & the Post-Disturbance Status
- Define the Target System
- Restart Generators & Rebuild Transmission Network

System Restoration (3 to 4 Hours)

- Energize Transmission Path
- Restore Load to Stabilize Generation and Voltage
- Synchronize Islands and Reintegrate Bulk Power System

Load Restoration (8 to 10 Hours)

- Load Restoration is the Governing Control Objective
- Load Pickup is Scheduled Based on Generation Availability
- Load Restoration is Effected in Increasingly Larger steps